



Submersible

StealthLite™ 2400 Flashlight

Popular with firefighters and adventure seekers. The unique easy slide thumb switch on the StealthLite 2400 Flashlight is easy to operate, even with gloves. The tough resin body is corrosion proof and resistant to extreme temperatures. The Xenon lamp is powered by 4 AA alkaline cells (included) for a bright beam that penetrates thick smoke, fog, and dust. Attach the StealthLite to one of our optional helmet light holder clips and you have a hands-free light for work or play. This light is submersible.

Minimum Pack 6 ea.

Packaged Weight: 8.1 oz.

Assorted Packs available - 2 black, 2 yellow, 2 orange.

StealthLite™ 2400 Flashlight Specifications

	High	
LIGHT SOURCE	Xenon	
BATTERIES	4 AA Alkaline (Included)	
CHARGE TIME	N/A	
VOLTAGE	6	
LENGTH	6.49" (16.5 cm)	
WEIGHT w/ BATTERIES	7.1 oz. (0.2 kg)	
WEIGHT w/o BATTERIES	3.5 oz. (0.1 kg)	

	FL1 STANDARD	High	
LIGHT OUTPUT		45 LUMENS	
RUNTIME (hours/min)		3h 45m	
BEAM DISTANCE (meters)		125m	
PEAK BEAM INTENSITY (candela)		3934cd	
WATER RESISTANT			

StealthLite™ 2400 Flashlight Configurations

Cat. #	Description
2400	StealthLite™ 2400 Flashlight (Carded)
2400PL	StealthLite™ 2400 Flashlight w/ Photoluminescent Shroud

NSN List

NSN #	Description
6230-01-462-9320	2400CNVG Black
6230-01-462-9320	2400 Black
6230-01-428-7464	2400C Yellow
6230-01-397-6341	2400C
6230-01-496-3639	2400 Zone 1 (Peli)
6230-01-525-9820	2400C Lime Green (2400-010-135)
6240-01-468-8407	2404 Lamp Module

StealthLite™ 2400 Flashlight Accessories

Cat. #	Description
700	Helmet Light Holder
710	Helmet Light Holder
711	Helmet Light Holder
712	Helmet Light Holder
750	Helmet Light Holder
760	Helmet Light Holder
770	Universal Helmet Light Holder
2404	StealthLite™ 2400 Xenon Lamp Module
2407	Cordura® Holster
2403PL	Photoluminescent Shroud

StealthLite™ 2400 Flashlight Approvals



Class I, Div. 2; Gp ABCD, T3C; Class II; Div. 2; Gp G.



Class I, Div. 2; Gp. ABCD, T3A.



10C-633-0



Intertek
3091325

US Class I, Div. 1, GP.D, CL.I, Zone 1, GP. IIA OPERATING TEMP. CLASS T3 CONFORMS TO STD. UL 783 Energizer E91 only

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: sales@pelican.com • www.pelican.com