

Uncontrolled document as of March 16, 2011. Refer to website for up to date specifications.

LIGHTS
2410
StealthLite Recoil LED



Submersible

StealthLite™ 2410 Recoil™ LED Flashlight

Same features as the [StealthLite 2400 Flashlight](#) but with the Recoil LED module that produces a true, bright collimated LED beam. The 2410 is corrosion proof, resistant to extreme temperatures, and submersible. It is powered by 4 AA alkaline cells (included). For hands-free operation, attach it to your hard hat with our optional helmet light holder.

Minimum Pack 6 ea.

Packaged Weight: 8.4 oz.

StealthLite™ 2410 Recoil™ LED Flashlight Specifications

High	
LIGHT SOURCE	Recoil LED
BATTERIES	4 AA Alkaline (Included)
CHARGE TIME	N/A
VOLTAGE	6
LENGTH	7" (17.8 cm)
WEIGHT w/ BATTERIES	7.3 oz. (0.21 kg)
WEIGHT w/o BATTERIES	3.7 oz. (0.1 kg)

StealthLite™ 2410 Recoil™ LED Flashlight Configurations

Cat. #	Description
2410	StealthLite™ 2410 Recoil™ LED Flashlight (Carded)
2410PL	StealthLite™ 2410 Recoil™ LED Flashlight (35mm) w/ Photoluminescent Shroud

StealthLite™ 2410 Recoil™ LED Flashlight Accessories

Cat. #	Description
700	Helmet Light Holder
710	Helmet Light Holder
711	Helmet Light Holder
712	Helmet Light Holder
750	Helmet Light Holder
760	Helmet Light Holder
770	Universal Helmet Light Holder
2407	Cordura® Holster
2413PL	Photoluminescent Shroud

FL 1 STANDARD		High
LIGHT OUTPUT		72 LUMENS
RUNTIME (hours/min)		7h 15m
BEAM DISTANCE (meters)		102m
PEAK BEAM INTENSITY (candela)		2622cd
WATER RESISTANT		

StealthLite™ 2410 Recoil™ LED Flashlight Approvals

IECEx

ITS.09.0017X Ex ia IIC T4 Ga, Ex ia IIIC T83°C Da IP66



Class I II III Div. 1 Grps. ABCDEFG Operating Temp. Class T4

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail:sales@pelican.com • www.pelican.com