

HIOKI 9290-10 Clamp-On Adapter



Easy-to-use, current to current transformer

- AC current up to 1500 A, secondary current 1/10 of primary

Basic specifications (Accuracy guaranteed for 1 year)

| | |
|------------------------------------|--|
| Rated primary current | AC 1000 A continued (Maximum 1500 A for 5 minutes or shorter) |
| Rated secondary current | AC 100 A (10 : 1 CT ratio) |
| Amplitude Accuracy | ±1.5% rdg. |
| Phase Accuracy | ±1.0° or less |
| Frequency characteristic | Amplitude: 20 Hz to 5 kHz: ±2.0 % rdg. (deviation from accuracy) Phase: 20 Hz to 5 kHz: ±1.0° or less (deviation from accuracy) |
| Max. rated voltage to earth | 600 V AC rms (insulated wire) |
| Core jaw dia. | φ55 mm (2.17 in) or 80 mm (3.15 in) × 20 mm (0.79 in) busbar |
| Dimensions, mass | 99.5 mm (3.92 in) W × 188 mm (7.40 in) H × 42 mm (1.65 in) D, 580 g (20.5 oz), cord length 3 m (9.84 ft) |
| Supplied accessories | Instruction manual ×1, Mark band ×6 |

Note: Cannot use with the Model CT 9279